



321, 11979 – 40th Street SE, Calgary, AB, Canada T2Z 4M3

tel: 403.243.9728 fx: 403.243.9749 tf: 866.652.2339

FIRE CADDY™ Product Specifications

FIRE CADDY™ GH5501

	Honda Engine
Horsepower	5.5
Displacement (cc / cu. in.)	163 / 9.9
Bore (in.)	2.7
Stroke (in.)	1.8
Weight (lbs.)	33.1
Oil Fill Capacity (oz.)	21
Valve	overhead
Cylinders	aluminum
Air Cleaner	paper
Ignition	Transistorized Magneto
Lubrication	splash

System and Pump

Suction Hose	20 feet of 3" non-collapsible
Discharge Hose	50 feet of ¾" high pressure rubber
Nozzle	Scotty air induction foam
Flow Rate @ full open nozzle	12 US gallons per minute @ 65 PSI
Free-Flow (2" secondary discharge)	100 US gallons per minute
Pressure Gauge	100 PSI liquid filled
Fire Suppressant Selector	0% to 6% @ 12 US gallons per minute, 65 PSI
Wheels	Solid Rubber
Hose Reel (for Discharge Hose)	Holds 50 feet of ¾" high pressure rubber, or 100 feet of 1" lay flat high pressure hose
Fire Suppressant	5 US gallons in integral tray
Weight (empty)	150 lbs
Weight (full w/ Fire Suppressant & motor fluids)	190 lbs
Dimension (Depth x Width x Height)	31" x 23" x 45" 79cm x 58cm x 114cm
Frame	Powder Coated Steel construction